



Irradiation Facilities at PSI

Wojtek Hajdas

Particle and Matter Dep. PSI Paul Scherrer Institut CH 5232 PSI Villigen Switzerland





Outline

Low energy PIF NEB

- New PIF at PROSCAN E<250 MeV
- Other PSI facilities
- Summary

•





Paul Scherrer Institut







Location of PSI







Experimental Hall and Accelerators





PROSCAN Area Layout





Main Accelerators and Injector 1





Injector 1 Phillips cyclotron Variable energy and particles Proton E_{max} = 72 MeV Operation until end of 2008: OPTIS, PIF, HI for Radiochemistry LISOR – material science





Proton Irradiation Facility

- PIF user-lab for radiation effects studies in electronics
- Realistic simulation of proton space environment
- Mono-energetic proton beams for radiation tests
- Calibration station for monitors and detectors
- Radiation qualification for space technologies
- Operates since 1992







PIF Typical Features

- Operation: weekends and "OPTIS" weeks late/night shifts
- Total beam-time 240 h/year for ESA and 240 h/year other users
- Wide range of proton energies and intensities
- Flexible, user-specific test arrangement
- Fast, uncomplicated set-up and operation
- Irradiations & sample position supervised by computer
- Sample frame Brookhaven, RADEF and HIF compatible
- Flux/Dosimetry ≈ 5 % absolute accuracy
- Irradiation in air





PIF Operation 2006 p.I

•	Irradiation period extend	Jan - Dec
0	Number of experiments	≈ 30
•	Visiting research groups	18
•	Days with beam	> 50
•	Beam blocks total	20
•	Beam shifts	54
•	Setup shifts	30
•	Development shifts	9







PIF Operation 2006 p.II

Beamtime and Area Utilization 2006

Area	PROSCAN	NEB	Total
Tests	10	21	31
Shifts	12	42	54











Main Users 2006

No Research Institution

- 1 IEEC, Barcelona, Spain
- 2 INFN, Bologna, Italy
- 3 HIREX Engineering, Toulouse, France
- 4 ABB, Lenzburg, CH
- 5 AME, Horten, Norway
- 6 INFN, Padova, Italy
- 7 INTA, Madrit, Spain
- 8 OAEW, Graz, Austria
- 9 Nuvonyx Europe, Marcousy, France

No Research Institution

- 10 ESTEC, Noordwijk, Netherlands
- 11 TEM, PSI Villigen, CH
- 12 Technical University of Denmark
- 13 Uni Zürich, CH
- 14 CERN, Genf, CH
- 15 CAEN Spa, Viareggio, Italy
- 16 ASTRIUM SAS, Velizy, France
- 17 E2V Technologies, Chlemsford, UK
- 18 IDA, Braunschweig, Germany





Main Experiments 2006

- STAR-Trackers
- Diodes
- RADFETS
- LISA Radiation Monitor
- Beam Loss Monitors
- Ionization Chambers
- Shielding Materials
- Activation of Shields
- Wireless Transmitters
- VME Controller

- SRAMs
- FPGAs
- CCDs
- Operational Amplifiers
- DC-DC converters
- Flash Memories
- Optocouplers
- Lasers Diodes
- Power Rectifiers
- High Voltage Devices





Low Energy PIF



Initial energy: 71 MeV Energy range: 6 to 71 MeV Max flux (6-71 MeV) $< 5.10^{8} \text{ p/cm}^{2}/\text{sec}$ Max beam spot < 90 mm diameter Beam uniformity 90% inside of 50 mm circle





Typical CERN Experiment



Ionization chambers, XY-table, positioning laser



Sample DUT frame, collimator, energy degrader





Using Vacuum Chamber



Chamber with NaI(TI) detectors and CH₂ target



Composite sample for S/C shielding





DAQ and Beam Monitoring p.I





Narrow beam spot (seen by damaged CCD)

Laptop parade during data taking



DAQ and Beam Monitoring p.II

NEB DAQ PANEL					
		> RUN <			
Run status	Run time /se	oc E	Save Data Flow	START STOP	lnitialize Holp
	Comment Energy / Run Nu	Me∀ 62.91 mber 1	Material LET MeV/cm	Si 19.24	Calibration
10-beam conter L-Fi	Targ	get id 📃 1	Total dose /rad	000E+0 0.00	Input Parameters
Flux p/cm2/sec	Dose rate rad/sec	Fluence p/cm2	Fluence/Dose %	Run Time %	⊻erify
0.00E+0	0.00E+0	0.00E+0	100.0-	100.0-	
		preset 2.00E+9	80.0-	80.0-	Bun
2E+8 4E	4+8 6E+8 8E+8 1E+9	Dose / rad	60.0-	60.0-	
Flu:	ix meter	0.00E+0	40.0-	40.0-	<u>O</u> utput/Results
1.0E+9-		Figure 1 2.65E+2	20.0-	20.0-	
8 1.0E+8-			0.0-		
3 1.0E+6-				10000.0	Quit
1.0E+5- 0 20	40 60 80 100 Run Time / sec			Close	

PAUL SCHERRER INSTITUT





New PROSCAN Cyclotron p.I

New PSI cyclotron for proton therapy from 2007
First beams in April 2007
Maximum energy 250 MeV
Input energy range 70 – 250 MeV (main degrader)
Intensity from the source 0.5 μA
GANTRY1, GANTRY2, OPTIS2, Exp. Area (PIF)
Commissioning of GANTRY1 and PIF completed





New PROSCAN Cyclotron p.II







Cyclotron, Degrader, Collimator



Degrader plates



SC Cyclotron and energy degrader

Insert with collimator





PIF @ PROSCAN Characteristics

• Currently available main energies: 235, 200, 150, 100, 70 MeV Lower energies with local degrader: e.g. 10-70 MeV Intensities: 2 nA (E>200 MeV), 10 nA (E<100 MeV) Operation during weekends, nights Standard PIF arrangement - merging Irradiation procedure similar to LE PIF





Beam Line and Setup







Experimental Area with PIF







Beam Parameters



Wide and narrow beam profiles; FWHM ca. 6 cm for wide beam





Dosimetry and Calibration



Plastic detectors

Ionization and wire chambers





Dosimetry Cross-check - SEU Mon



ESA - SEU Monitor			
File ?			
Tests to Execute on AT60142 Write AT60142 All 1 Read AT60142 1143 Word Errors 1144 Bit Errors Launch Test	Errors Distribution Toleran Bit 3 Bit 1 162 144 Bit 2 141 Bit 4 138	Status : Dre: 10% Image: 10% BR:0 A160142 Bith 5 Em 148 A160142 Bith 5 Em 148 A160142 Bith 5 Em 148 A160142 Bith 5 Em 149 A160142 Bith 5 Em 141 A160142 Bith 5 Em A160142 Bith 5 Em A160142 Bith 5 Em	Clear Status Window xs: 141 xs: 141 xs: 138 xs: 152 xs: 129 xs: 144 xs: 148 sc: 148 sc: 1143 orguence Completed 143
Reference Data Source : Proton		Atmel AT60142F-DC1 4Mbit S	RAM
Proton Energy : All	1.0E-12		
User Points Error Number :	1.0E-13	× ×	×
Energy (MeV) : Tilk (Deg.) : 0	1.0E-14		
Add Point Delete Point Bit Cross-Section Energy	1.0E-15		
2.300E-14 39.3 2.379E-14 20.5 1.040E-14 10.8 2.713E-14 100.0 2.725E-14 100.2	1.UE-16 0 60	120 180	240 300
Refresh	× PIF • User		

ESA SEU Monitor

Flux value comparison





Degrader, Collimator







XY-Table









Utilities and Safety



Shaft for individual users cables



Flat beam lasers



Neutron and ionization detectors

6th LHC Radiation Workshop 29-30 Nov 2007





Users Measurement Barrack







Experimental Setup



Controller for PROBA 3 (under control ...)



Optocouplers (displacement effects)





Infrastructure, Cables, Connectors Number of BNC, HV, RJ45, D9 and D25 (RS) cables is free for the users Individual cables (15-20 m) can be put via shaft on the roof with the PIF barrack Scopes, power supplies, multimeters, monitors etc. are available (reserve early pls) Special extra structures, shielding: lead and paraffin blocks, must be requested in advance





33

Test Arrangement







Selecting Energy and Intensity

- Energy on target set using local PIF degrader (requires calibration)
- Selection of different primary energy still performed by PIF operator (requires verification of positions and profiles)
- Application for user-setting of the beam intensity is currently under tests





_ 🗆 🗡

Running Proton Exposure Test

	■ PIF_DAQ	<u> </u>		🐼 RUN			_ 🗆
	DAQ started 11-29-2007, 18:43:40 Output File PIF2007_11_29h18m43s Target	40_DAQ.txt	$\langle X X \rangle$	Status TARGET ID Comment	Run # 1 M	laterial Si ▼	Verify Inp Log Flux
	Run No. 1 Comment Beam setup and calibration TARGET ID Test 1 Material Si T Energy	Accept		Energy / Me∨ Time /s 0.00 0	Est. ti	me to finish/s	RUN On
	Beam Energy /MeV 200.00 Energy@Target/ MeV 100.00 Fluence/Dose Ymm 0.0 0.0 Fluence /cm2 Use Dose /rad 0.0 1.000E+10 10000E+0 Use Current Eos. Ymm	edd Goos Easto Edd		Fluence /p/cm2 Dose /ra 0.000E+0 0.000E- Flux /p/cm2/s Dose rat 0.000E+0 0.000E-	ad LE +0 Cr 0.(0.(0.(0.(T /MeV/cm)00E+0 oss sect./cm-1)00E+0 tal Dose /rad)00E+0	Next Pause Open BeamValve
	Calibration Factor1 /p/cm2/c Offset1 c/s Use Calib. Panel 1.000E+0 0.00 Value Factor2 /p/cm2/c Offset2 c/s closest 1.000E+0 0.00	Close Max run time /s 1.000E+4		5.00E+7 0.00E+0 Flux /cm2/s	Fluence/Dose% 100.0- 1 80.0-	Time% Max Run tir 00.0-	Preset Values ne/s X/mm 0.0
	Input display/selection Input File			8.0E+1- 6.0E+1- 4.0E+1- 2.0E+1- 2.0E+1-	60.0- 40.0- 20.0- 0.0-	60.0- 40.0- 20.0- 0.0- 50.000E+0 0.000E+0 0.000E+0	/cm2 Y /mm 0.0 Degr. /mm 0
W1	LET / MeV/cm -1.00 Degrader / mm -1.00	th LHC Do	diati	0.0E+0- 0 25 50 75 100 Time /s	0.0	0.0 Split Current /	<u>Close</u>





Pre Irradiation Procedures

Similar as before Short test description (as on the pif-web) List of attendants and arrival times Highly recommended: early registration at PSI virtual user office Advanced finishing of the dosimetry class Timely request of extra equipment, shield etc. Contact information about material transport





Post Irradiation Procedures

- DUTs and materials check by the radiation protection officers
- Storage in the Active Magazine
- Post-measurements possible in selected rooms
- Reserve enough time some services e.g. SU don't work on weekends





Station of Radiation Protection SU

Studio B for post-tests inside Zone





Beam Schedule

Program presented on the web gives available and booked periods

http://pif.web.psi.ch/LAP_files/PIF_Calender_Jan_Dec_07.pdf

Early request of at least 3 months highly recommended

Kaler	nder																											
									Р	IF C	ale	endar f	rom Ju	ly to) De	cei	mber 20	007										
W		Julv		w			August		w		5	Septemb	ber	W			Oktober		W		1	lovemb	er	w		D	ecember	r
	Sun	1		31	Wed	- 1				Sat	1	booked		40	Mon	1			44	Thu	1				Sat	1		
27	Mon	2		-	Thu	2				Sun	2				Tue	2				Fri	2				Sun	2		
	Tue	3			Fri	- 3			36	Mon	3				Wed	3				Sat	3			49	Mon	3		
-	Wed	4			Sat	- 4				Tue	- 4				Thu	-4				Sun	-4				Tue	4		
	Thu	5			Sun	- 5				Wed	- 5		booked		Fri	-5			45	Mon	-5				Wed	5		
	Fri	6 booked		32	Mon	- 6				Thu	6		booked		Sat	- 6				Tue	- 6				Thu	6		
	Sat	7 booked			Tue	- 7				Fri	- 7				Sun	-7				Wed	- 7				Fri	7		
	Sun	8 booked			Wed	8				Sat	8			41	Mon	8				Thu	- 8				Sat	8		booked
28	Mon	9 LE			Thu	9				Sun	- 9				Tue	9				Fri	-9				Sun	9		booked
	Tue 1	0 booked			Fri	10			37	Mon	10				Wed	10				Sat	10			50	Mon	10	LE	
	Wed 1	1 booked			Sat	-11				Tue	-11				Thu	11				Sun	11				Tue	11	booked	
	Thu 1	2			Sun	12				Wed	12				Fri	12			46	Mon	12				Wed	12	booked	
	Fri 1	3		33	Mon	13				Thu	13				Sat	13				Tue	13				Thu	13		
	Sat 1	4			Tue	-14				Fri	-14				Sun	14				Wed	14				Fri	14	booked	
	Sun 1	5			Wed	15				Sat	15			42	Mon	15				Thu	15				Sat	15	booked	
29	Mon 1	6			Thu	16				Sun	16				Tue	16				Fri	16				Sun	16	booked	
	Tue 1	7			Fri	-17			38	Mon	17				Wed	17				Sat	17			51	Mon	17		
	Wed 1	8			Sat	18				Tue	18				Thu	18				Sun	18				Tue	18		
	Thu 1	9			Sun	19				Wed	19				Fri	19			47	Mon	19	LE			Wed	19		
	Fri 2	10		34	Mon	20				Thu	20				Sat	20				Tue	20	booked			Thu	20		
	Sat 2	1	_		Tue	21				Fri	21				Sun	21				Wed	21				Fri	21		
	Sun 2	22	_		Wed	22				Sat	22			43	Mon	22	LE			Thu	22	booked			Sat	22		
30	Mon 2	3			Thu	23				Sun	23				Tue	23	booked			Fri	23	booked			Sun	23		
	Tue 2	4		-	Fri	24				Mon	24	LE			Wed	24	booked			Sat	24	booked	booked		Mon	24		
	Wed 2	15			Sat	25			39	Tue	25	booked			Thu	25	booked			Sun	25	booked	booked	52	Tue	25		
	Thu 2	16			Sun	26				Wed	26	booked			Fri	26	booked		48	Mon	26				Wed	26		
	Fri 2	7	_	35	Mon	27	LE			Thu	27	booked	-		Sat	27	booked			Tue	27				Thu	27		
	Sat 2		_		Tue	28				Fri	28	booked	booked		Sun	28	DOOKED			wed	28				Fri	28		
	Sun 2	8	_		Wed	29	booked			Sat	-29	booked	Dooked	44	Mon	29				Thu	29				Sat	29		
31	Mon 3			-	Thu	30	booked			Sun	-30	booked	booked		Tue	30				Fri	30				Sun	30		
	Tue la	1			Fn	-31	DOOKED								vved	31									MON	-31		
LE	Lo	w Energy I	PIF OPTIST	Veek /I	NEB (C	Jven	night, after	OPTIS, Tu	e-⊩n	~18.0	JU - I	J6.0U)			booke	d	User Opera	ation Booke	d				Facility (Nt	:B) av	/a lable	2		
HE	H	gh Energy	PIF - Prosci	an (We	ekend	s, af	ter Medical	Science, F	ri - M	on ~1	7.00	- 06.00)			booke	d	User Opera	ation Booke	d				High-Energ	ју-Fa	cility (P	105/	:an) not av	ailable





PIF Parameters in Brief

- Low and high energy PIF merged in PROSCAN Experimental Area
- Initial energies (now): 235, 200, 150, 100 and 70 MeV
- Lower energies set with a degrader: ca. 10 up to 70 MeV
- Maximum beam intensity above 200 MeV: 2 nA
- Maximum beam intensity below 100 MeV: 10 nA
- Maximum flux at any primary energy 2-5.10⁸ p/sec/cm² (wide beam)
- Beam profiles are Gaussian-form with FWHM≅6 cm or focused
- Irradiations, devices and sample positioning by the computer
- DUT frame 25 x 25 cm2 RADEF and HIF facilities compatible





Further Irradiation Options at PSI Synchrotron Light Source E.g. high intensity X-rays with energies of few keV Cold neutrons at SINQ Atmospheric neutrons at SINQ • Very high dose beams: Isotope Production station station in Injector I NEA (Lisor) Radiochemical analysis of secondary isotopes





Atmospheric Neutrons

- PSI accelerator can be used for atmospheric neutrons e.g. SINQ
- Studies required to assess feasibility, two locations identified
- Spectral shape based on MC very promising for ICON and NEUTRA







Summary

- New proton facility constructed at PSI
- Energy range extended up to 250 MeV
- Beam time during nights and weekends
- Commissioning completed, first test performed
- User-friendly and easy to operate
- Other facilities at PSI:
 - synchrotron light (e.g. X-rays)
 - cold and atmospheric neutrons
 - very high dose proton beams
 - Radiochemical isotope analysis





Thank You!