### Cosmic ray test certification of the first 100 CMS endcap RPCs and the corresponding construction database

On behalf of

A. Ball, J-P. Chatelain, I. Crotty, A. Sharma, <u>W. Whitaker</u> CERN CH 1211, Geneva, Switzerland

Y. Ban, J. Cai, H. Liu, S. Qian, Q. Wang, Y. Ye, J. Ying Peking University, Beijing, China

B. Hong , S. J. Hong , K. S. Lee, S. Park, K. S. Sim, KODEL, Seoul, S. Korea

W. Van Doninck<sup>1</sup>, Vrije Universiteit Brussel, Brussels, Belgium

> S. Akimenko<sup>1</sup> IHEP, Protvino, Russia

A. Marinov<sup>1</sup> University of Sophia, Sophia, Bulgaria

Z. Aftab, M. S. Khan, T. Solaija Pakistan Atomic Energy Commission, Islamabad, Pakistan


> A. Colaleo, G. Iaselli, F. Loddo, M. Maggi INFN Bari, Itlay

> > W. Whitaker

<sup>1</sup> presently at CERN


# **CMS** Experiment

RPC construction and testing are divided into barrel and endcap regions




# RE 1 Disk

### **RPCs** are positioned in concentric circles





## **Three Trigger Sectors**



Sijian will describe construction next

W. Whitaker



## Test Stands

### Cosmic Stand

**Efficiency/Cluster size** 

High Voltage Monitor Stand Long Term Stability



10 chambers Round about time 3-4 days

10 chambers Round about time 7-15 days

W. Whitaker October 2005





## Testing with Cosmic Rays

#### Cosmic stand. Top and Bottom layers TITTITI scintilators. RE1-2-078 Possibility to put 10 chambers inside to test them with 23 RE1-2-030 cosmics 1 RE1-2-079

W. Whitaker

|-----20 cm-






W. Whitaker October 2005



## RE1/3 Efficiency at 9.3 kV




# Chamber

W. Whitaker



## RE1/2 Efficiency at 9.3 kV




W. Whitaker



### Acceptance Criteria:


## *Efficiency* >95%



W. Whitaker




**Strips Profile** 



#### Using only 2 scintilators from the top and 2 form the bottom layer

W. Whitaker






Coincidence with 2 scintilators from top, 2 from bottom and small counter placed on sector B.

W. Whitaker






W. Whitaker




### **Time Distribution**



W. Whitaker




## Cluster Size RE1/2



W. Whitaker




#### Mean Cluster Size Distribution for HV = 9400V (N = 79 chambers) RP1/2: Mean Cl. S. = 2.245, RMS Cl. S. = 0.461; RP1/3: Mean Cl. S. = 1.981, RMS Cl. S. = 0.160



W. Whitaker



#### **Efficiency and Cluster Size**



Scanning for efficiency and Cluster size values at different voltages.



## Test Stands

### Cosmic Stand

**Efficiency/Cluster size** 


High Voltage Monitor Stand Long Term Stability



10 chambers Round about time 3-4 days

10 chambers Round about time 7-15 days


W. Whitaker October 2005





#### Current Distribution for HV = 9400V (Bottom Gaps of the Chambers)

Mean Current = 0.859µA, RMS Current = 0.836µA




W. Whitaker




#### Current Distribution for HV = 9400V (Bottom Gaps of the Chambers)

RE1/2: Mean I = 0.769µA, RMS I = 1.004µA; RE1/3: Mean I = 0.952µA, RMS I = 0.622µA





#### Current Distribution for HV = 9400V (Top Gaps of the Chambers=67) RE1/2: Mean $I = 1.171 \mu A$ , RMS $I = 1.281 \mu A$ ; RE1/3: Mean $I = 1.126 \mu A$ , RMS $I = 1.127 \mu A$





### Check-lists

- Chamber traveller contains:
- Preparation list (15 items)
- Production checklist (50 items)
- Cosmic test checklist (15 items)
- Lab sign out checklist (10 items)
- Some duplications


### Attention to detail ensured by checklists

37 Make sure that the screen box and the HCP box have the same number.
38 De burr the sharp edges of the slot and holes after modification.

W. Whitaker



Taking Data




W. Whitaker October 2005




# Database

http://forwardrpc.cern.ch/cms\_forward\_rpc/index.htm






### **Construction Database**






Cosmic tests & DAQ •Efficiency •Chamber Certification Database •Dynamic Plots •Searchable Worldwide



W. Whitaker



### **Continuous Monitoring of Ambient Conditions**






# Continuous H.V. Monitoring

Recording the HV currents every 2 min, and store the data in to the Database.

Including the environment conditions. Temperature and Humidity



W. Whitaker



# Plans for Database

- Currently working on a fully implemented Oracle database
  - Already copying data to an Oracle database as mentioned before
  - Graphic interface is in the preliminary stages of development
  - Interface development will continue as time permits.

W. Whitaker



# Plans for Construction Database

• 2005:


ALL chambers certified

• 2006:

Chamber tests completed and data are stored for the life of the experiment

W. Whitaker

## Installation





# The Collaboration

#### **CHINA**

Yanlin Ye Sijin Qian Jun Ying Quanjin Wang Yong Ban Jianxin Cai Hongtao Liu Ge Xue Zhiuwa

#### PAKISTAN

Hafeez Hoorani M. Irfan Asghar Ijaz Ahmed Tariq Solaija M. Shariq Khan Zia Aftab Javed Alam Jan Muhammad Usman Mian Iftikhar

### KOREA

Sungkeun Park Kwang-Souk Sim Byungsik Hong Seongjong Hong Kyong Sei Lee

### ITALY

Giuseppe Iaselli Flavio Loddo Marcello Maggi Marcello Abbrescia Anna Colaleo Carlo Pinto Michele Papagni

#### CERN

Austin Ball Serguei Akimenko J.P. Chatelain Ian Crotty Archana Sharma Andrey Marinov Walter Vandoninck William Whitaker +

15 temp students/visitors

W. Whitaker